# **Product Information Declaration**

# **Tredsafe Stairnosings Vinyl Stairs Range**

#### **Range Description**

This Jacobsen Product Information Declaration (PID) applies to the accessories range sold by Jacobsen as Tredsafe Stairnosings Vinyl Stairs

#### **Identifiers**

See individual sku codes under identifiers

#### **Scope and Limitations of Intended Use**

$\overline{v}$	Antistatia Environment
<b>✓</b>	High Traffic
<u>~</u>	Residential

- ✓ Commercial

  X Low Traffie

  X Food Prep Areas
- ✓ Interior
  ✓ Exposed Sunlight

  X Clean Room
- ExteriorWet Areas

With Wheels

- X Under Floor Heating
- Over Existing Floor

# R

# **Stability**

X Ramp/Entry

Relevant NZBC Clause	Product Performance	
B2.3.1(c)	-	
Residential	-	
Commercial	5 Years	
Industrial	-	

# C

#### **Protection from Fire**

Relevant NZBC Clause	Product Performance
C4.3	
C4.3 (a) Wall	-
C4.3 (b) Floor	-

# D

#### Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	-
Level Surface (Dry)	Acceptable Solution
Suitable for food prep	-

# Ε

#### **Moisture**

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

# F

#### **Safety of Users**

Relevant NZBC Clause	Product Performance
F2.3.1	Not Tested
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	-

# G

#### **Services and Facilities**

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

# Н

#### **Energy Efficiency**

Relevant NZBC Clause	Product Performance
Thormal Pating	Not tostad

# X

#### **Warnings and Bans**

Building Act 2004	Product Performance
Section 26	True

# **Supporting Documents**

All supporting documents can be found on the Jacobsen website, <u>jacobsen.co.nz</u> or by this QR code



Page 1 of 3 V:040524

# **Product Information Declaration Tredsafe Stairnosings Vinyl Stairs Range**

#### B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if:

- 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
- 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

#### C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

#### D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

#### E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

#### E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

#### E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

#### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

#### G3.3.2

Spaces for food preparation and utensil washing shall have:

#### (b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

#### G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than FF

#### G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

#### H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

# **Note**

It is expected that **Tredsafe Stairnosings Vinyl Stairs** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Page 2 of 3 V:040524

# **Product Information Declaration Tredsafe Stairnosings Vinyl Stairs Range**

#### **Identifiers**

This JPID covers all colours from Tredsafe Stairnosings Vinyl Stairs including:

AA114 11887 AA216 11910 UP117 11926 AA107 11883

AA202 (CLEARANCE - limited

availability) 11905 AA115 11888 AA110 11886 AA223 (CLEARANCE - limited

availability) 19079 AA108 11884

AA209 (CLEARANCE - limited

availability) 11908

AA208 (CLEARANCE - limited

availability) 11907 AA130 TSAA130



Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN:

9429040403328





Product Manufacturer: Tredsafe Country of Origin: New Zealand

Page 3 of 3