Product Information Declaration

Regal Park Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the carpet range sold by Jacobsen as Regal Park

Identifiers

X Over Existing Floor

See individual sku codes under identifiers

Scope and Limitations of Intended Use

| ✓ | Residential | ✓ | Commercial | ✓ | Interior | × | Exterior |
|----------|------------------------|----------|------------------------|----------|------------------|---|-------------|
| ~ | High Traffic | × | Low Traffic | / | Exposed Sunlight | X | Wet Areas |
| × | Antistatic Environment | × | Food Prep Areas | × | Glean Room | × | With Wheels |

B

Stability

X Ramp/Entry

| Relevant NZBC Clause | Product Performance |
|----------------------|--|
| B2.3.1(c) | Jacobsen Carpets are covered by the NZ Consumer Guarantees Act of 1993. |
| Residential | Extra Heavy Duty - 6 star |
| Commercial | Medium Duty - 2 Star |
| Industrial | |

C

X Under Floor Heating

Protection from Fire

| Relevant NZBC Clause | Product Performance |
|----------------------|---------------------------------|
| C4.3 | |
| C4.3 (a) Wall | - |
| C4.3 (b) Floor | CHF 1.7 kW/m2 (ISO 9239.1:2010) |

D

Access

| Relevant NZBC Clause | Product Performance |
|------------------------|---------------------|
| D1.3.3 | |
| Level Surface (Wet) | - |
| Level Surface (Dry) | Acceptable Solution |
| Suitable for food prep | - |

Ε

Moisture

| Relevant NZBC Clause | Product Performance |
|----------------------|-------------------------------|
| E3.3.3 | Impervious and easily cleaned |
| E3.3.5 | Impervious and easily cleaned |
| E3.3.6 | Water resistant |
| NZBC/AS1 | - |

F

Safety of Users

| Relevant NZBC Clause | Product Performance |
|----------------------|-------------------------------------|
| F2.3.1 | Not Tested |
| | Does not encourage bacterial growth |
| | Phthalate-free |
| Indoor Air Quality | Good |

G

Services and Facilities

| Relevant NZBC Clause | Product Performance | |
|----------------------|---------------------|--|
| G3.3.2 (b) | Water resistant | |
| G6.3.2 | - | |
| | | |

Н

Energy Efficiency

| Relevant NZBC Clause | Product Performance | | |
|----------------------|---------------------|--|--|
| Thermal Rating | Not tested | | |

X

Warnings and Bans

| Building Act 2004 | Product Performance | |
|-------------------|---------------------|--|
| Section 26 | - | |

Supporting Documents

All supporting documents can be found on the Jacobsen website, <u>jacobsen.co.nz</u> or by this QR code



Page 1 of 3 V:180524

Product Information Declaration Regal Park Range

B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if:

- 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
- 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that **Regal Park** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Page 2 of 3 V:180524

Product Information Declaration Regal Park Range

Identifiers

This JPID covers all colours from Regal Park including:

Raw Umber 556 24308 Oatmeal 555 24307 Mushroom 558 24306 Gunsmoke 554 24305 Gravel 553 24304 Ashen Grey 552 24303 Antique White 551 24302 Shoreliner 557 24516

Sustainability

| Rating System | Rating | Product Performance |
|-----------------------------------|------------------|---------------------|
| Green Star Design & | Credit 12 | - |
| As Built NZ (V1) | Credit 20 | 1 Point |
| | Credit 21 | - |
| Green Star | Credit 13 | - |
| Interiors NZ (V1) | Credit 20 | 1 Point |
| | Credit 21 | - |
| Green Star Performance NZ (V1) | Credit 21 | 1 Point |
| Homestar V5 | HC 7 | - |
| | EN 3 | - |
| Homestar V4 | Mat-1 | - |
| | Mat-2 | - |
| Environmental Product Dec | celeration (EPD) | - |
| Embodied Carbon Emissio | n Data | - |

Environmental Credentials



Jacobsen[®]

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN:

9429040403328

Product Manufacturer: **Beaulieu** Country of Origin: Australia

Page 3 of 3 V:180524