# **Jacobsen**<sup>®</sup>

## **Product Information Declaration**

## **Bouclé Range**

#### **Range Description**

This Jacobsen Product Information Declaration (PID) applies to the carpet range sold by Jacobsen as Bouclé

#### **Scope and Limitations of Intended Use**

,	Residential	~	Commercial
,	High Traffic	×	Low Traffic
<	Antistatic Environment	×	Food Prep Areas
<	Ramp/Entry	×	Under Floor Heating

#### **Identifiers**

See individual sku codes under identifiers

/	Interior
/	Exposed Sunlight
ĸ	<del>Clean Room</del>

**Over Existing Floor** 

Exterior X

> Х Wet Areas

X With Wheels

✓ |✓ |× |× |×



#### B **Stability**

Relevant NZBC Clause	Product Performance
B2.3.1(c)	Jacobsen Carpets are covered by the NZ Consumer Guarantees Act of 1993.
Residential	Extra Heavy Duty - 5 star
Commercial	Medium Duty - 2 Star
Industrial	-

#### С **Protection from Fire**

Relevant NZBC Clause Product Performance

Х

C4.3		
C4.3 (a) Wall	-	
C4.3 (b) Floor	-	

#### D Access

Relevant NZBC Clause	Product Performance		
D1.3.3			
Level Surface (Wet)	-		
Level Surface (Dry)	Acceptable Solution		
Suitable for food prop			

Suitable for food prep

## Е

#### **Moisture**

Relevant NZBC Clause	Product Performance		
E3.3.3	Impervious and easily cleaned		
E3.3.5	Impervious and easily cleaned		
E3.3.6	Water resistant		
NZBC/AS1	-		

#### F **Safety of Users**

-	
Relevant NZBC Clause	Product Performance
F2.3.1	86.3 μg/m2.h (ISO 10580)
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	Good

#### G **Services and Facilities**

Relevant NZBC Clause	Product Performance	
G3.3.2 (b)	Water resistant	
G6.3.2	-	

#### Н **Energy Efficiency**

Relevant NZBC Clause	Product Performance

Thermal Rating

Not tested

#### Х **Warnings and Bans**

Building Act 2004 **Product Performance** 

Section 26

#### **Supporting Documents**

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



Page 1 of 3

## Product Information Declaration Bouclé Range

#### B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

#### (c)

5 years if: 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and

2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

#### C3.4

Surface Linings

#### (b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

#### D1.3.3

Access routes shall:

#### (d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

#### E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

#### E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

#### E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

## Note

It is expected that **Bouclé** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

#### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

#### G3.3.2

Spaces for food preparation and utensil washing shall have:

#### (b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

#### G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

#### G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

#### H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

## Product Information Declaration Bouclé Range

#### Identifiers

This JPID covers all colours from Bouclé including:

Sarinen 25301 Ovie 25303 Mokum 25308 Maymo 25304 Jacqueline 25307 Coco 25306 Atticus 25305

#### Sustainability

Rating System	Rating	Product Performance
Green Star Design &	Credit 12	1 Point
As Built NZ (V1)	Credit 20	1 Point
	Credit 21	-
Green Star	Credit 13	1 Point
Interiors NZ (V1)	Credit 20	1 Point
	Credit 21	-
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	1 Point
	EN 3	-
Homestar V4	Mat-1	-
	Mat-2	1 Point
Environmental Product Decele	-	
Embodied Carbon Emission Data		-

#### **Environmental Credentials**



Jacobsen®

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN: 9429040403328 Product Manufacturer: **EC Carpets** Country of Origin: Australia