

## Product Information Declaration

# Shaw Contract Beyond Range

### Range Description

This Jacobsen Product Information Declaration (PID) applies to the carpet range sold by Jacobsen as **Shaw Contract Beyond**

### Identifiers

See individual sku codes under [identifiers](#)

### Scope and Limitations of Intended Use

|  |   |   |   |
|--|---|---|---|
| <input checked="" type="checkbox"/> Residential            | <input checked="" type="checkbox"/> Commercial          | <input checked="" type="checkbox"/> Interior            | <input checked="" type="checkbox"/> Exterior    |
| <input checked="" type="checkbox"/> High Traffic           | <input checked="" type="checkbox"/> Low Traffic         | <input checked="" type="checkbox"/> Exposed Sunlight    | <input checked="" type="checkbox"/> Wet Areas   |
| <input checked="" type="checkbox"/> Antistatic Environment | <input checked="" type="checkbox"/> Food Prep Areas     | <input checked="" type="checkbox"/> Clean Room          | <input checked="" type="checkbox"/> With Wheels |
| <input checked="" type="checkbox"/> Ramp/Entry             | <input checked="" type="checkbox"/> Under Floor Heating | <input checked="" type="checkbox"/> Over Existing Floor |   |

## B Stability

| Relevant NZBC Clause | Product Performance                |
|----------------------|------------------------------------|
| B2.3.1(c)            | 5 Year Commercial Limited Warranty |
| Residential          | -                                  |
| Commercial           | Heavy Duty                         |
| Industrial           | -                                  |

## C Protection from Fire

| Relevant NZBC Clause | Product Performance               |
|----------------------|-----------------------------------|
| C4.3                 |                                   |
| C4.3 (a) Wall        | -                                 |
| C4.3 (b) Floor       | 30oz - 6.0kW/m2 (ISO 9239.1:2010) |

## D Access

| Relevant NZBC Clause   | Product Performance |
|------------------------|---------------------|
| D1.3.3                 |                     |
| Level Surface (Wet)    | -                   |
| Level Surface (Dry)    | Acceptable Solution |
| Suitable for food prep | -                   |

## E Moisture

| Relevant NZBC Clause | Product Performance           |
|----------------------|-------------------------------|
| E3.3.3               | Impervious and easily cleaned |
| E3.3.5               | Impervious and easily cleaned |
| E3.3.6               | Water resistant               |
| NZBC/AS1             | -                             |

## F Safety of Users

| Relevant NZBC Clause | Product Performance |
|----------------------|---------------------|
| F2.3.1               | ≤0.5 mg/m3          |
|                      | -                   |
|                      | Phthalate-free      |
| Indoor Air Quality   | Optimal             |

## G Services and Facilities

| Relevant NZBC Clause | Product Performance |
|----------------------|---------------------|
| G3.3.2 (b)           | Water resistant     |
| G6.3.2               | -                   |

## H Energy Efficiency

| Relevant NZBC Clause | Product Performance |
|----------------------|---------------------|
| Thermal Rating       | Not tested          |

## X Warnings and Bans

| Building Act 2004 | Product Performance |
|-------------------|---------------------|
| Section 26        | -                   |

## Supporting Documents

All supporting documents can be found on the Jacobsen website, [jacobsen.co.nz](http://jacobsen.co.nz) or by this QR code



# Product Information Declaration

## Shaw Contract Beyond Range

---

### B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (c)  
5 years if:
1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
  2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

### C3.4

Surface Linings

#### (b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

#### D1.3.3

Access routes shall:

#### (d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

#### E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

#### E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

#### E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

### G3.3.2

Spaces for food preparation and utensil washing shall have:

#### (b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

#### G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

#### G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

### H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

---

## Note

It is expected that **Shaw Contract Beyond** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

# Product Information Declaration Shaw Contract Beyond Range

## Identifiers

This JPID covers all colours from Shaw Contract Beyond including:

|  |                                       |
|--|---------------------------------------|
| Ridge 11 ft Circle R016G-15580         | Moss 12 x 15 ft Rectangle R015G-15326 |
| Moss 11 ft Circle R016G-15326          | Dune 12 x 15 ft Rectangle R015G-15105 |
| Dune 11 ft Circle R016G-15105          | Ridge 6 X 9 ft Rectangle R013G-15580  |
| Ridge 6 X 9 ft Rectangle R013G-15580   | Moss 6 X 9 ft Rectangle R013G-15326   |
| Moss 6 X 9 ft Rectangle R013G-15326    | Ridge 8 X 10 ft Rectangle R014G-15580 |
| Dune 6 X 9 ft Rectangle R013G-15105    | Moss 8 X 10 ft Rectangle R014G-15326  |
| Ridge 12 x 15 ft Rectangle R015G-15580 | Dune 8 X 10 ft Rectangle R014G-15105  |

## Sustainability

| Rating System                           | Rating    | Product Performance |
|---|-----------|---------------------|
| Green Star Design & As Built NZ (V1)    | Credit 12 | 1 Point             |
|   | Credit 20 | 1 Point             |
|   | Credit 21 | -                   |
| Green Star Interiors NZ (V1)            | Credit 13 | 1 Point             |
|   | Credit 20 | 1 Point             |
|   | Credit 21 | -                   |
| Green Star Performance NZ (V1)          | Credit 21 | -                   |
|   |           |                     |
| Homestar V5                             | HC 7      | 1 Point             |
|   | EN 3      | -                   |
| Homestar V4                             | Mat-1     | -                   |
|   | Mat-2     | 1 Point             |
| Environmental Product Declaration (EPD) |           | -                   |
| Embodied Carbon Emission Data           |           | -                   |

## Environmental Credentials



# Jacobsen®

Jacobsen 41D Morrin Road,  
St Johns, 1072  
0800 800 460  
[jacobsen.co.nz](http://jacobsen.co.nz)  
[sales@jacobsen.co.nz](mailto:sales@jacobsen.co.nz)

NZBN:  
9429040403328

# ShawContract®

Product Manufacturer: Shaw Contract  
Country of Origin: United States of America