# Jacobsen®

## **Product Information Declaration**

## **Regupol Classic Range**

#### **Range Description**

This Jacobsen Product Information Declaration (PID) applies to the rubber range sold by Jacobsen as Regupol Classic

#### **Scope and Limitations of Intended Use**

~	Residential	~	Commercial
~	High Traffic	_ x	Low Traffic
×	Antistatic Environment	_ x	Food Prep Areas
×	Ramp/Entry	_ x	Under Floor Heating



Interior

**Identifiers** 

- Exposed Sunlight

See individual sku codes under identifiers

- Х Clean Room
- Х **Over Existing Floor**

. . . . .

- Exterior X
- Х Wet Areas
- With Wheels

### В **Stability**

-		
Relevant NZBC Clause	Product Performance	
B2.3.1(c)	5 Years	
Residential	Extra Heavy Duty	
Commercial	Extra Heavy Duty	
Industrial	Heavy Duty	

### С **Protection from Fire**

Relevant NZBC Clause	Product Performance	
C4.3		
C4.3 (a) Wall	-	
C4.3 (b) Floor	4mm - CRF 6.2 kW/m2 (ISO 9239.1:2010), 8mm CRF 5.0 kW/m2 (ISO 9239.1:2010)	

### D Access

Relevant NZBC Clause	Product Performance	
D1.3.3		
Level Surface (Wet)	SRV 39 (AS4586:2013)	
Level Surface (Dry)	Acceptable Solution	
Suitable for food prep	-	

#### Ε **Moisture**

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

## F

#### **Safety of Users** Relevant NZBC Clause Product Performance F2.:

F2.3.1	2.3 mg/m2/hr ASTM D5116
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	Good

## G

#### **Services and Facilities**

Relevant NZBC Clause	Product Performance	
G3.3.2 (b)	Water resistant	
G6.3.2	Approx. 19dB ISO 140	

### Н **Energy Efficiency**

Relevant NZBC Clause	Product Performance
Thermal Rating	Good

### X **Warnings and Bans**

Building Act 2004	Product Performance	
Section 26	-	

#### **Supporting Documents**

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



## **Product Information Declaration Regupol Classic Range**

#### B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

#### (c)

5 years if: 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and

2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

#### C3.4

Surface Linings

#### (b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

#### D1.3.3

Access routes shall:

#### (d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

#### E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

#### E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

#### E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

## Note

It is expected that **Regupol Classic** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

#### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

#### G3.3.2

Spaces for food preparation and utensil washing shall have:

#### (b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

#### G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

#### G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

#### H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

## **Product Information Declaration Regupol Classic Range**

#### Identifiers

This JPID covers all colours from Regupol Classic including:

Sidon (Core) 4mm 11771 Goa (Core) 4mm 11770 Manaus (Core) 4mm 11768 Palau (Core) 4mm 11767 Amsterdam (Core) 4mm 11769 Goa (Core) 8mm 11784 Melbourne (Core) 8mm 11782 Amsterdam (Core) 8mm 11779 Palau (Core) 8mm 11778 Berlin (Core) 8mm 11778 Berlin (Core) 8mm 11777 Berlin (Core) 8mm 11777 Berlin (Core) 8mm 11779 Melbourne (Core) 4mm RGCLME4 Auckland (Core) 4mm RGCLAU4 Perth (Tone) 8mm RGCLPE8 Lhasa (Tone) 8mm RGCLPE8 Perth (Tone) 4mm RGCLPE4 Lhasa (Tone) 4mm RGCLLH4 Sydney (Tone) 8mm RGCLSY8 Nome (Tone) 8mm RGCLNO8 Kush (Tone) 8mm RGCLKU8 Bern (Tone Berlin) 8mm RGCLBE8 Auckland (Tone) 8mm RGCLAU8 Sydney (Tone) 4mm RGCLSY4 Nome (Tone) 4mm RGCLNO4 Kush (Tone) 4mm RGCLNO4 Kush (Tone) 4mm RGCLKU4 Bern 4mm (Tone) RGCLBE4

#### Sustainability

Rating System	Rating	Product Performance
Green Star Design &	Credit 12	-
As Built NZ (V1)	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 0.5
Green Star	Credit 13	-
Interiors NZ (V1)	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 0.5
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	1 Point
	EN 3	1.5 Points
Homestar V4	Mat-1	2 Point
	Mat-2	1 Point
Environmental Product Deceleration (EPD)		-
Embodied Carbon Emission Data		-

#### **Environmental Credentials**



PVC FREE RECYCLA





Product Manufacturer: **Regupol** Country of Origin: DEU

## Jacobsen®

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN: 9429040403328