

## Technical Datasheet

# Acoustic comfort underlayer Elafono

UNDERLAY & OVERLAY SOLUTIONS

## DESCRIPTION

Loose-laid underlayer made of cork to enhance acoustic comfort choosing the natural route.

### Key features:

- High-performance acoustic insulation reducing both impact sound reduction up to 15 dB, and in-room noise up to 65 dB, with any compact linoleum.
- 100% natural and sustainable backing layer.
- Highly flexible to ease installation.
- Superior performances in static indentation, thermal resistance and underfoot comfort.

### Subfloor type & applications:

- Commercial applications.
- Concrete surfaces.

### Compatible flooring:

- Compact linoleum in rolls.
- Homogeneous vinyls in rolls.

### Main segments of application:



## TECHNICAL INFORMATION

### Product

Size (mm)	30 length x 2 width
Thickness (mm)	2.0
Total density (g/m <sup>2</sup> )	1,450

### Packaging

Min. order	1 roll (also available as 608 x 608mm pre-cuts for access floor producers)
------------	--

## CLEANING & MAINTENANCE

No cleaning or maintenance required.



## INSTALLATION

- Unroll and acclimatize in the room for at least 24 hours (> 18°)
- Switch off 48 hours before installation the underfloor heating system, and remain it off at least 48 hours after.
- The subfloor must be flat, level, clean, without marks, sound, dry, solid, hard, smooth and not exposed to moisture.
- Install underlayer with the jute backing facing upwards and edge to edge
- Install Elafono and Linoleum flooring in the same direction. Use acrylic adhesive for linoleum flooring. Pay attention to the waiting time for such adhesive - read the installation instructions.
- The joints of the Elafono and of the linoleum must have a gap of at least 50cm.

## ARTICLE CODE

	SAP Code	EAN Code
 Brown	1861030	8022211100548