



**JACOBSEN
BRINGS YOU**

**Concrete +
Composed**

Luxury Vinyl Tile Residential & Commercial

Suitable for all residential and commercial applications such as:

- > Healthcare
- > Retail
- > Education
- > House
- > Workplace
- > Cafe
- > Restaurant

Technical Data

Characteristic	Standard	
Construction	ATSM F1700	LVT Class III, Type B
Surface Treatment	ExoGuard™	
Overall Thickness	EN ISO 24346	5.5mm
Wear Layer Thickness	EN ISO 24340	0.51mm
Residual Indentation	ATSM F1914	Pass
Dimensional Stability	EN ISO 23999	Pass
Colour Fastness to Light	ATSM F1515	Pass
Castor Chair Test	EN ISO 4918	No Change
Critical Radiant Flux	EN ISO 9239-1	6.5 kW/m ²
Chemical Resistance	ATSM F925	Pass
Slip Resistance	AS 4586:2013	SRV 37
Acoustic Impact Sound Reduction	ASTM E492	21dB

Concrete



Forged - V2 Misty Quart - V2 Tempered - V3

Composed



Bison - V2 Buckeye - V4 Cascade - V3 Chalet - V2
Grand Teton - V4 Spice - V4 Stoney Oak - V3

Variation Guide

V1 - Uniform V2 - Slight V3 - Moderate V4 - Substantial
Refer to Variation Guide sheets for in-situ images

Structure

1. ExoGuard Finish

Added protection against scratching, staining and abrasion.

2. Clear 0.51mm Wear Layer

Protects against premature product aging.

3. High-Resolution Image

Creates a stunning visual with depth, it is laminated directly to the COREtec XRC core.

4. COREtec XRC Extruded Core


Waterproof and dimensionally stable, with a density of 1900-2000 kg/m³, the rigid core protects the top layers from indentation.

Size & Packaging

	Size (mm)	Tiles Per Pack	m ² Per Pack
Planks	1222 x 182	12	2.66
Tiles	470 x 610	10	2.87

Benefits

- Excellent acoustic reduction, 21dB.
- Can be installed glue down or floating.
- Mini micro bevelled edge.
- Fast installation with limited floor preparation.
- Immediate occupancy after installation.
- Can be installed in residential kitchens and bathrooms.



5. Attached Cork Underlayment

Provides added sound dampening from foot traffic and floor to floor sound transfer.

6. Integrated Locking Edge

Eliminates the need for wet adhesives, floating installation limits floor prep and eliminates telegraphing.

Jacobsen® | ShawContract®

Talk to one of our experts, or visit our website:

0800 800 460 | customer.services@jacobsen.co.nz | jacobsen.co.nz

