

PRIMO SD

TECHNICAL DATA

| CERTIFICATION & CLASSIFICATION | STANDARDS | PRIMO SD |
|--------------------------------|--------------|---|
| Type of floor covering | ISO 10581 | Static dissipative pressed homogeneous vinyl flooring |
| Classification | EN ISO 10874 | Commercial: 34 Industrial: 43 |
| Wear layer binder content | ISO 10581 | Type I |

TECHNICAL CHARACTERISTICS

| | | |
|------------------|----------------------------|---|
| Total thickness | EN ISO 24346 | 2.0 mm |
| Total weight | EN ISO 23997 | 3000 g/m ² |
| Form of delivery | EN ISO 24341 Sheet (rolls) | Approx. 23 lm x 200 cm Art. no. 21012 ___ 3 digit colour number |
| | EN ISO 24342 Tiles (box) | 61 x 61 cm - 16 tiles/box = 5.95 m ² Art. no. 21016 ___ 3 digit colour number |

PERFORMANCES FOR CE MARKING REQUIREMENTS (EN 14041)

| | | |
|----------------------------|---|---|
| Declaration of Performance | EN 14041 | 0019-0047-DoP-2013-07 |
| Reaction to fire | EN 13501-1 EN ISO 9239-1 EN ISO 11925-2 | Class B _i -s1 ≥ 8 kW/m ² Pass |
| Electrostatic properties | EN 1815 | < 2 kV |
| Thermal resistance | EN 12667/DIN 52612 | Approx. 0.01 m ² K/W |
| Slip resistance | EN 13893 / BS 7976-2 | ≥ 0.3 / Low risk of slip |

TECHNICAL PERFORMANCES

| | | |
|-------------------------|--------------------|--|
| Residual indentation | EN ISO 24343-1 | Required value: ≤ 0.10 mm Best measured value*: 0.03 mm |
| Slip resistance | DIN 51130 | R9 |
| Ease of decontamination | ISO 8690 | Good |
| Bacteria resistance | EN ISO 846: Part C | Does not favour growth |
| Chemical resistance | ISO 26987 | Good resistance |
| Castor chair | ISO 4918 | Suitable |
| Flexibility | ISO 24344 | Pass |
| Dimensional stability | EN ISO 23999 | ≤ 0.40 % for rolls / ≤ 0.25 % for tiles |
| Light fastness | EN ISO 105-B02 | ≥ 6 |
| Electrical insulation | VDE 0100, Part 600 | R _i ≥ 5x10 ⁴ Ω |
| Electrical resistance | EN 1081 | R _i ≤ 10 ⁸ Ω |
| Seam strength | EN 684 | Average value: ≥ 240 N/50 mm Individual values: ≥ 180 N/50 mm |
| Underfloor heating | | Suitable - max. 27°C |

ENVIRONMENTAL PERFORMANCES

| | | |
|---------------------|----------------------------------|---|
| Total VOC emissions | ISO 16000-9 / Indoor air quality | ≤ 10 µg/m ³ (after 28 days) / Platinum |
|---------------------|----------------------------------|---|

COLOURS

8

The above information is subject to modification for the benefit of further improvement. (04/18)

*For information - not binding.

According to the European Regulation N° 305/2011 for CE Marking, the Declarations of Performance are available on our website www.tarkett.com

Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.

Colours of the products shown in the photos or samples are indicative only. There may be differences in colours, gloss and embossing structure between the products sold and photos or samples.

CUSTOMS TARIFF : 4820 5000 00

