

## Inclusive


Collection	<b>Community</b>	
Style Number	<b>4068V</b>	
Construction	<b>Multilayer SPC With Attached Cork Underlayment</b>	
Class / ASTM F3261	<b>Class III, Type B</b>	
Attached Underlayment	<b>Cork</b>	
Finish	<b>ExoGuard™</b>	
	U.S.	Metric
Nominal Dimensions	<b>7 in w x 48 in l</b>	<b>18 cm w x 122 cm l</b>
Actual Dimensions	<b>7.17 in w x 48.03 in l</b>	<b>18.21 cm w x 122.00 cm l</b>
Wear Layer Thickness	<b>20 mil (0.02 in)</b>	<b>0.51 mm</b>
Overall Thickness	<b>0.217 in</b>	<b>5.5 mm</b>
Edge Profile	<b>Micro-Bevel</b>	
Installation Type	<b>Click</b>	
Installation	<b>Floating Or Direct Glue</b>	
Recommended Adhesive	<b>LOKWORX+ RESILI, 4151, LOKWORX+ RESILI or LG4100 4G</b>	



## Packaging

Pieces per Carton	<b>12 pcs</b>	
Area per Carton	<b>28.68 sq ft</b>	<b>2.66 sq m</b>
Weight per Carton	<b>48.41 lbs</b>	<b>21.96 kg</b>

## Recommended Installation Method



## Coordinating Products

COREtec: Expression

Carpet Tile: Knotted Tile, Process Tile, Back Weave Tile, Exchange Tile, Heddle Tile, Flat Weave Tile

Broadloom: Embrace, Share

## Performance + Testing

Static Load (ASTM F970)	<b>Passes</b>
Dimensional Stability (ASTM F2199)	<b>Passes</b>
Resistance to Heat (ASTM F1514)	<b>Passes</b>
Resistance to Light (ASTM F1515)	<b>Passes</b>
Resistance to Chemicals (ASTM F925)	<b>Passes</b>
Smoke Density (ASTM E662, Flaming Mode)	<b>Passes</b>
Radiant Panel (ASTM E648)	<b>Passes, Class I</b>
Coefficient of Friction (ASTM D2047, Slip Resistance)	<b>≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces</b>

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

## Warranties

[15 Year Commercial Limited Warranty](#)

## Product Transparency

Shaw Contract is dedicated to providing clients with a building chemistry that's safe and dependable. Working together, we will help you meet your goals as they pertain to material health. COREtec® products are UL Certified with an Industry-Wide EPD and are assessed for impacts on human health and the environment.

## Attributes + Certifications

Environmental Product Declaration (EPD)	<b><a href="#">3rd Party Certified in Accordance with ISO 14025, EN 15804, &amp; ISO 21930:2017</a></b>
FloorScore®	<b>Certified</b>
Total Recycled Content	<b>0% (Pre-Consumer 0%   Post-Consumer 0%)</b>
Country of Origin	<b>Peoples Republic of China</b>

## LEED Contribution Credit

MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration	<b>RFCi Industry Average EPD (50%)</b>
EQ Credit: Low Emitting Materials Option 1: Product Category Calculations	<b>FloorScore Certified</b>

[Installation Guidelines](#)

[Maintenance Guidelines](#)

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

